

SK-760 Single Input HD Modulator

This single input high definition MPEG-4 RF modulator is fully featured with IR return path and HDMI loop through. Boasting a large LED display with full control of all functions via the front panel keys. The unit is simple to use and pre-set for use in Australia.

Parameters such as LCN, Channel Name, Network ID are all adjustable. The unit is perfect for distributing any high definition source around hotels, clubs, homes.

Features

- HDMI Loop Through
- Selectable HDMI or CVBS Inputs
- IR Return Path (Targets Included)
- MPEG4 H.264 HD
- Maximum 1080P Resolution
- Fully Adjustable RF output
- HDCP Supported
- Silent Operation (No Fan)
- Programmable LCN, NID and Channel Name
- Aluminium Case





SK-760 Single Input HD Modulator

Input	
Channels	Single
Source	HDMI + CVBS
HDMI Resolution	576i, 720p, 1080i, 1080p
RF Output	
Frequency	50-860MHz
MER	35dB
Output Level	70-100dBuV
Modulation	
Standard	DVBT
Bandwidth	6,7,8 MHz
Constellation	QPSK, 16QAM, 64QAM
Guard Interval	1/4, 1/8, 1/16, 1/32
Code Rate	1/2, 2/3, 3/4, 5/6, 7/8
Carrier	2K, 8K
Compression	
Video	MPEG-4 AVC, H.264
Power	
Plug Pack	240VAC/12VDC 1.5A
Connections	HDMI IN x1, HDMI Out x1, CVBS in x1 RF In x1, RF Out x1, IR x1 2.1mm DC Jack x1, Mini USB x1
Physical	
Dimensions	210x130x40mm
Weight	500g
Temperature Range	0-45°C
Package Includes	1x SK-760, 2x IR Blaster, 1x Power Pack, 1x USB cable, 1x Instruction Disk



www.satking.com.au

Specifications Subject to Change Without Notice